

PRODUCT DESCRIPTION

iForm 281 UV photosensitive resin

YOUSU iForm 281 is an industrial-grade UV resin designed to have outstanding toughness. It can be used to print heavy-duty models as well as functional production parts. This resin can be used in domestic printers as well as in industrial printers with a bigger printing volume.

ATTRIBUTES		
Resin model	YOUSU iForm281 photosensitive resin for LCD	
Grade	iForm281	
Color	black white	
Viscosity(25℃)	130-150cps	
Wavelength	405nm	
MECHANICAL PROPERTIES		
Tensile strength	42 -45 MPa	ASTM D638
Elongation at break	30-40%	ASTM D638
Notched impact strength	35J/m	ASTM D256
Heat deflection temperature(0.45MPa)	70℃	ASTM D648
Hardness	75-80D	ASTM D2240
PRINTING INFORMATION		
	Color Screen	Mono Screen
Normal exposure time	8s	2.5-3s
Bottom exposure time	60s	25-30s
Bottom layer	6	3
Layer thickness	0.05mm	

POST-PROCESSING STEP

1. Once the printing is completed, products need to rinse in isopropyl alcohol and dry normally.
2. Post-curing is required for **some products** to reach its **highest** possible strength and stability.
3. Supports are removed from the products for a clean finish.

Any technical information provided and recommendations made herein are intended to assist customers in determining whether our products are suitable for your applications. We request that you must test our products before use and accepted at your own risk. Neither Yousu nor its affiliates shall be responsible for the use of this information, or of any product, method or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. We do not guarantee results, freedom from patent infringement, or suitability of resultant products for any suggested application with respect to the use of any formula or material described herein.